

**MINI ELECTRIC HOIST, EWH SERIES**



European Standard Attestation CE, GS, EMC

With urgent stop switch and reinforced breaking switch with position limit

Protection class up to IP54, with thermal protection device

MODEL		EWH-200	EWH-250	EWH-300	EWH-400	EWH-500	EWH-600	EWH-700	EWH-800	EWH-1000	EWH-1200
Voltage (V)		220/230/240									
Frequency		50/60 Hz									
Lifting Capacity	Single hook	100 kg	125 kg	150 kg	200 kg	250 kg	300 kg	350 kg	400 kg	500 kg	600 kg
	Double Hook	200 kg	250 kg	300 kg	400 kg	500 kg	600 kg	700 kg	800 kg	1000 kg	1200 kg
Input Power (W)		480	510	600	950	1020	1200	1250	1300	1600	1800
Lifting Speed (m/min)	Single hook	10	10	10	10	10	10	8	8	8	8
	Double Hook	5	5	5	5	5	5	4	4	4	4
Lifting Height (m)	Single hook	12	12	12	12	12	12	12	12	12	12
	Double Hook	6	6	6	6	6	6	6	6	6	6
Packing (pcs/carton)		2pcs(470x370x160mm)			2pcs(520x420x170mm)					1pc(560x250x350mm)	
G.W./N.W. (kgs)		24/22	24/22	26/24	35/33	35/33	35/33	39/37	39/37	33/32	33/32

**MINI ELECTRIC HOIST, EWH-E SERIES**



Latest European Standard Attestation with up and down position limit CE, GS, EMC, RoHS

With urgent stop switch and reinforced braking switch with position limit.

Protection class up to IP54, with thermal protection device

MODEL		EWH-200E	EWH-250E	EWH-300E	EWH-400E	EWH-500E	EWH-600E	EWH-700E	EWH-800E	EWH-990E
Voltage (V)		220/230/240								
Frequency		50/60 Hz								
Capacity	Lifting Single hook	100 kg	125 kg	150 kg	200 kg	250 kg	300 kg	350 kg	400 kg	495 kg
	Double Hook	200 kg	250 kg	300 kg	400 kg	500 kg	600 kg	700 kg	800 kg	990 kg
Input Power (W)		480	510	600	950	1020	1200	1250	1300	1600
Speed (m/min)	Lifting Single hook	10	10	10	10	10	10	8	8	8
	Double Hook	5	5	5	5	5	5	4	4	4
Height(m)	Lifting Single hook	12	12	12	12	12	12	12	12	12
	Double Hook	6	6	6	6	6	6	6	6	6
Packing (pcs/carton)		2pcs (490x430x160mm)			2pcs (520x480x170mm)			2pcs (540x505x195cm)		1pc(560x250x350mm)
G.W./N.W. (kgs)		26/24	26/24	26/24	37/35	37/35	37/35	41/39	41/39	35/33

**MINI ELECTRIC HOIST, EWH-L SERIES**



European Standard Attestation CE, GS, EMC

With urgent stop switch and reinforced breaking switch with position limit

Protection class up to IP54, with thermal protection device

MODEL		EWH-200L	EWH-300L	EWH-400L	EWH-500L
Voltage (V)		220/230/240			
Frequency		50/60 Hz			
Lifting Capacity	Single hook	100 kg	150 kg	200 kg	250 kg
	Double Hook	200 kg	300 kg	400 kg	500 kg
Input Power (W)		1020	1300	950	1020
Lifting Speed (m/min)	Single hook	20	20	20	20
	Double Hook	10	10	10	10
Lifting Height (m)	Single hook	12	12	12	12
	Double Hook	6	6	6	6
Packing (pcs/carton)		2pcs(520x420x170mm)	2pcs(520x250x170)	1pc(560x250x350mm)	
G.W./N.W. (kgs)		35/33	39/37	33/32	33/32