


**FARM JACK**

- Construction, agriculture and industrial application where long travel is required for lifting, pulling, pushing or clamping.
- Adjustable top bracket used for clamping.
- Safety shear pin protects lifting nose and dropping of load if jack is overloaded.
- Load is supported when activated in either direction.
- 3/4" lift with each handle stroke.
- 

	<b>FARM JACK</b>					
	Item	Size/Inch	Min. H (mm)	Lifting H (mm)	Max. H (mm)	N.W. (kg)
	FJ-20	20"	130	550	680	11
	FJ-33	33"	130	570	700	12
	FJ-48	48"	130	940	1070	13
FJ-60	60"	155	1195	1350	14	

**Hydraulic Bottle Jack**



MODEL	Capacity (Ton)	Min. H. (mm)	Lifting H. (mm)	Adjust H. (mm)	N.W. (kg)	Q'ty/Ctn (pcs)	Meas. (cm)	20°FCL (pcs)
TH1004	10	190	110	60	5.5	4	30.5x29.5x22	3200
TH1204	12	190	100	60	6.7	4	30.5x32x22	2600
TH1604	16	190	105	60	7.7	2	31.5x17x22	2300
TH2004	20	190	90	60	9.8	2	34.5x19.5x22	1800
TH3204	32	220	115	-	12.3	2	37.5x19x24.5	1463

**Hydraulic Bottle Jack Standard**

Plastic box



(B)



T0202



T0402



T0602



T0802



T1002



T1202



T1202S



T1602



T2002



T2002S



T2502



T3202



T5002



T10002

MODEL	Capacity (Ton)	Min. H. (mm)	Lifting H. (mm)	Adjust. H. (mm)	N.W. (kg)	Q'ty/Ctn (pcs)	Meas. (cm)	20°FCL (pcs)
T0202	2	158	90	60	2.4	10	51x24x19	7300
T0202B	2	158	90	60	2.4	6	34x34x25.5	4536
T0402	3 or 4	180	110	60	3.3	5	58x13x21	5300
T0402B	3 or 4	180	110	60	3.3	6	55x22x30	3906
T0602	5 or 6	200	125	80	4.5	5	63x14x23	3920
T0602B	5 or 6	200	125	80	4.5	4	40x27x33	3024
T0802	8	200	125	80	5.6	4	28x28x23	3140
T1002	10	200	125	80	6.3	2	30x15x23	2790
T1202	12	210	125	80	7.5	2	32x16x24	2340
T1202S	Low 12	170	85	50	6.4	2	32x16x24	2750
T1602	15 or 16	225	140	80	9	2	33x17x26	1958
T2002	20	235	145	60	11.5	2	37x18x27	1530
T2002S	Low 20	190	95	50	9.6	2	37x18x22	1800
T2502	25	250	160	-	12.5	2	37x18x27	1400
T3202	30 or 32	285	180	-	18	2	38x20x31	970
T5002	50	285	180	-	23	1	22x21x32	765
T5002H	Heavy 50	285	180	-	33	1	25x22x33	530
T10002	100	335	180	-	78	1	54x44x35	230

**Manual Hydraulic Cylinder With Toe-lift**



Model	Capacity (ton)	Stroke (mm)	Coll height (mm)	Ext.height (mm)	Toe height (mm)	Toe-lift base LxW(mm)	N.W. (kg)
HYL-5	5	117	230	317	18	69x45	8.5
HYL-10	10	147	282	387	22	98x55	20
HYL-20	20	152	310	462	25	123x63	31
HYL-30	30	155	330	485	28	149x60	42
HYL-50	50	155	370	525	40	190x75	85

**Hydraulic Bottle Jack with safety valve**



MODEL	Capacity (Ton)	Min. H. (mm)	Lifting H. (mm)	Adjust. H. (mm)	N.W. (kg)	Q'ty/Ctn (pcs)	Meas. (cm)	20FCL (pcs)
T0204	2	158	90	60	2.4	10	51x24x19	7300
T0204B	2	158	90	60	2.4	6	34x34x25.5	4536
T0404	3 or 4	195	125	60	3.5	8	47x26x23	5032
T0404B	3 or 4	195	125	60	3.5	6	55x22x30	3860
T0604	5 or 6	200	125	80	4.5	6	39x28x23	3918
T0604B	5 or 6	200	125	80	4.5	4	40x27x33	3024
T0804	8	236	160	80	6.7	4	31x29x27	2628
T1004	10	240	160	80	7.5	4	31x29x27	2348
T1204	12	245	160	80	8.5	2	36x17x27	2070
T1604	15 or 16	250	160	80	10.4	2	36x17x27	1692
T2004	20	250	160	80	11.5	2	37x18x27	1530
T3204	30 or 32	285	180	-	18	2	38x20x31	970
T5004	50	285	180	-	23	1	22x21x32	765

**Hydraulic Bottle Jack lower height**



MODEL	Capacity (Ton)	Min. H. (mm)	Lifting H. (mm)	Adjust. H. (mm)	N.W. (kg)	Qty/Ctn (pcs)	Meas. (cm)	20FCL (pcs)
T0205L	2	150	80	55	2.2	10	52x23.5x18	8100
T0205LB	2	150	80	55	2.2	6	33x33x24.5	6300
T0405L	3 - 4	158	90	60	2.8	8	46x24.5x20	6400
T0405LB	3 - 4	158	90	60	2.8	6	34.5x34x28	5100
T0605L	5 - 6	195	125	60	3.7	8	48x25.5x22.5	4500
T0605LB	5 - 6	195	125	60	3.7	6	37.5x35x30	4260
T0805L	8	197	125	60	4.2	6	38x25.5x22.5	3750
T0805LB	8	197	125	60	4.2	4	39.5x26x30.5	3560
T1005L	10	205	125	60	5.4	4	27.5x27.5x23.5	3100
T1005LB	10	205	125	60	5.4	4	40.5x28x30	3280
T1205L	12	205	125	60	6.2	4	29.5x29.5x23.5	2650
T1605L	15-16	210	125	60	6.8	4	31x30x24	2450
T2005L	20	225	140	60	9.4	2	32x19x25.5	1800
T2005LB	20	225	140	60	9.4	2	31.5x21x33	2560
T3205L	30-32	245	145	-	13	2	35x20x27.5	1250
T5005L	50	285	180	-	23	1	23x19x31	690

## Floor Jack



Color Box(A)



Plastic Box(B)



MODEL	Capacity (Ton)	Min. H. (mm)	Lifting H. (mm)	Max. H. (mm)	N.W. (kg)	Qty/Ctn (pcs)	Meas. (cm)	20FCL (pcs)
TFL1A	2	135	200	335	9.0	1	45.5x21x14.5	2100
TFL1B	2	135	200	335	9.0	1	48x23.5x15.5	1900
TFL2A	2	135	200	335	8.0	1	45.5x20x14.5	2100
TFL2B	2	135	200	335	8.0	1	48x23.5x15.5	1900
TFL3A	2	125	175	300	7.0	1	43x21x13.5	2500
TFL3B	2	125	175	300	7.0	1	45x22.5x14.5	2300
TFL4A	2	125	175	300	6.5	1	43x21x13.5	2500
TFL4B	2	125	175	300	6.5	1	45x22.5x14.5	2300



TFL320



TFL321



TFL322



TFL323



TFL324



TFL325



TFL326

MODEL	Capacity (Ton)	Min. H. (mm)	Lifting H. (mm)	Max. H. (mm)	N.W. (kg)	Qty/Ctn (pcs)	Meas. (cm)	20FCL (pcs)
TFL320	3	190	342	532	16	1	64x22x21	950
TFL321	3	135	360	495	28	1	67x37.5x20	500
TFL322	3	135	360	495	30	1	67x37.5x20	500
TFL323	3	135	360	495	32	1	67x37.5x20	500
TFL324	3	135	360	495	34	1	67x37.5x20	500
TFL325	3	135	385	520	36	1	77x39x21	430
TFL326	3	135	385	520	36	1	77x39x21	430

**Air Bottle Jack**



T0507Q



T1207Q



T2007Q



T2007LQ



T3207Q



T2207Q

MODEL	Capacity (Ton)	Min. H. (mm)	Lifting H. (mm)	Adjust. H. (mm)	Max. H. (Mm)	N.W. (kg)	Qty/Ctn (pcs)	Meas. (cm)	20FCL (pcs)
T0507Q	5	210	140	80	430	6	1	20x17x23	2100
T1207Q	12	250	165	80	495	10	1	24x18x28	1350
T2007Q	20	260	170	80	510	17	1	26x20x28	1000
T2007LQ	20 Low	210	100	80	390	15	1	26x21x23	1150
T3207Q	32	280	195	-	475	24.5	1	30x30x22	700
T2207Q	22	250+20	130+80	80	435+100	36	1	64x35x30	410