


Stainless Connecting Link



Stainless connecting link, made of T316 stainless, precision cast, idea to joint 2 pieces of chain together or joint the chain to an attachment.

DIMENSIONS

	ITEM	A	B	C	D	WLL	WT
	S0460-0005	3/16"	0.35"	0.70"	1.09"	400	0.03
	S0460-0006	1/4"	0.43"	0.84"	1.30"	600	0.04
	S0460-0008	5/16"	0.48"	0.95"	1.60"	1,000	0.09
	S0460-0010	3/8"	0.60"	1.15"	1.87"	1,500	0.14
	S0460-0013	1/2"	0.75"	1.45"	2.43"	2,000	0.28
	S0460-0016	5/8"	0.95"	1.90"	3.15"	4,000	0.57

DETAILS

- 316 Stainless Steel

Stainless Clevis Slip Hook



Stainless clevis slip hook with safety latch, load rated (not for overhead lifting) made of A316 precision cast, ideal to use with stainless proof coil chain.

Item#	WLL	Specification	Ship Weight
331S-X-06	660 lb	1/4" pin, 7/16" clevis opening, 1" hook opening	0.42lbs.
331S-X-08	1,500 lb	5/16" pin, 1/2" clevis opening, 1-1/16" hook opening	0.76lbs.
331S-X-10	2,000 lb	3/8" pin, 5/8" clevis opening, 1-5/16" hook opening	1.18lbs.
331S-X-13	3,000 lb	1/2" pin, 3/4" clevis opening, 1-3/4" hook opening	2.36lbs.

Stainless Eye Slip Hook



Stainless eye slip hook with safety latch, made of A316 stainless, precision cast, load rated (not for overhead lifting) ideal to use with proof coil chain.

Item#	WLL	Specification	Ship Weight
325S-X-06	660 lb	1/2" eye I.D., 1" hook opening	0.35lbs.
325S-X-08	1,100 lb	5/8" eye I.D., 1-1/16" hook opening	0.55lbs.
325S-X-10	1,540 lb	3/4" eye I.D., 1-5/16" hook opening	0.90lbs.
325S-X-13	2,850 lb	1" eye I.D., 1-11/16" hook opening	1.90lbs.

Stainless proof Coil Chain A316



Stainless steel proof coil chain made of A316 stainless, commercial grade, size range from 1/8" to 3/4", can be cut per feet.

Item#	WLL	Specification	Weight
660S-A-03	375 lb	1/8" x 0.29" inside width x 0.78" inside length	0.38lbs.
660S-A-05	830 lb	3/16" x 0.40" inside width x 0.94" inside length	0.42lbs.
660S-A-06	1,450 lb	1/4" x 0.47" inside width x 1.24" inside length	0.70lbs.
660S-A-08	2,200 lb	5/16" x 0.50" inside width x 1.28" inside length	0.95lbs.
660S-A-10	3,000 lb	3/8" x 0.57" inside width x 1.38" inside length	1.40lbs.
660S-A-13	4,600 lb	1/2" x 0.79" inside width x 1.54" inside length	2.60lbs.
660S-A-16	5,800 lb	5/8" x 0.75" inside width x 2.22" inside length	3.30lbs.
660S-A-20	9,000 lb	3/4" x 0.95" inside width x 2.76" inside length	5.50lbs.

Stainless proof coil chain A304



Proof coil stainless steel chain, made of A304 stainless, commercial grade, size from 3/1" to 1/2", can be cut by foot.

Item#	WLL	Specification	Ship Weight
662S-10	42 lb	0.13" x 0.31" link width x 0.85" link length	0.15lbs.
662S-12	28 lb	0.097" x 0.23" link width x 0.86" link length	0.08lbs.
662S-14	16 lb	0.08" x 0.20" link width x 0.63" link length	0.05lbs.
662S-16	10 lb	0.06" x 0.15" link width x 0.52" link length	0.03lbs.

Overhead lifting stainless chain



German made, high quality, reliable overhead lifting stainless chain (Grade 50), dimensions are similar to DIN 5687-1. Can be cut by foot.

Item#	WLL	Specification	Weight
660S-50-05	1,100 lb	5mm x 6.50mm inside width x 18.50mm inside length	1.19lbs.
660S-50-06	1,650	6mm x 7.80 inside width x 18mm inside length	1.76lbs.
660S-50-08	2,750 lb	8mm x 10.40 mm inside width x 24 mm inside length	3.00lbs.
660S-50-10	4,400 lb	10mm x 13mm inside width x 30mm inside length	4.85lbs.
660S-50-13	7,040 lb	13mm x 16.90mm inside width x 39mm inside length	8.36lbs.
660S-50-16	11,000 lb	16mm x 20.80mm inside width x 48mm inside length	12.50lbs.
660S-50-18	13,860 lb	18mm x 24.30mm inside width x 54mm inside length	16.06lbs.

Stainless long link chain A316



Stainless long link chain, light weigh, great for barrier, made of T316 stainless, sold by foot.

Item#	WLL	Specification	Ship Weight
660S-A-03-L	360 lb	0.12" x 0.25" inside width x 1.02" inside length	0.12lbs.
660S-A-05-L	880 lb	0.18" x 0.40" inside width x 1.38" inside length	0.28lbs.
660S-A-06-L	1,200 lb	0.23" x 0.45" inside width x 1.66" insided length	0.40lbs.